



## Specifications

<b>Description</b>	<b>HINO 300 Series-XZU 6.5T GVW Cargo</b>
<b>Model</b>	<b>New Gen XZU710L</b>
GVW (kg)	6500
Pay load (kg)	3600
Engine Type	4.0 L, 4 cyl. Turbo Charged with Intercooler with Electronic Control Common Rail
Engine Power / Torque	140 PS / 392 Nm
Clutch Type / Dia	Dry single plate, hydraulic control / 300 mm dia
Gear Box	5F + 1R, Synchronesh
Brake - Front/Rear	Front: Drum Brake Rear: Drum Brake
Suspension - Front/Rear	Semi-elliptic leaf springs with shock absorbers
Steering	Hydraulic assisted power steering
Wheel type	6 Stud Disc Type
Dimensions L x W x H (mm)	6120 x 1995 x 2210
Wheel Base(mm)	3430
Turning circle radius (mm)	5800
Fuel Tank capacity (L)	100
Max Speed (kmph)	112
Gradeability (%)	41.2
Tyre & Rim size	7.50R16-10PR
Battery / Alternator	Battery:12V x 2, Alternator: 24V 60 A
Cabin / Seating Capacity	Wide Cab
Others	
Tiltable cabin	With
Factory fitted A/C	With
Cargo Body from Japan	L x W x H (mm) 4355 x 2085 x 380
Radio AM/FM+CD Player	With
Spare wheel carrier	With
Load sensing valve	With
PTO	Without