



Toyota Fortuner 2.7 SR5 Premium A/T

Technical details:

Model Code	TGN51L-EKPSKV
Origin:	Indonesia
Engine	Petrol, 2694 cc, 4 cyl. In-line DOHC 16V, VVTi, EFi, Catalyst converter for unleaded fuel
Max output/Torque	158 HP/5200 rpm, 24.6/3800 rpm
Transmission	4-speed automatic (floor), Full time 4x4, TORSEN Limited Slip Differential (Centre)
Tires and disc wheel	Tire 265/65R17 on 6.5J 17" alloy wheels
Brakes front/rear	Vent. Disc/Drum w/LSPV
Suspension front/rear:	Double Wishbone / 4-link Coil
Seats	7 seats (2+3+2), fabric
Fuel tank capacity	80L

Standard Equipment:

- ABS brakes
 - Air-conditioner, Dual with heater
 - Airbag driver/passenger
 - AM/FM radio w/single CD, MP3 and 6 speakers + USB and AUX port
 - Adjustable seat belt anchors, front
 - Bumper front and rear, color keyed
 - Combination meters
 - Console box with lid and cup holder
 - Digital clock, Door handles, chromed
 - Driver's seat vertical adjustable
 - Engine immobilizer, Floor mats new design
 - Front seat belts 3PELRx2 + pre-tensioner
 - Front fog lamps, Front map lamps, Fuel lid opener
 - Green laminated windshield
 - Halogen head lamps, Head lamp leveling
 - Head rests front 2 and rear 2+2, Heater, front
 - High mount stop lamp LED, Inner rear view mirror day/night
 - Meter illumination control, Mud guards front and rear
 - Over fenders, color keyed, Power mirrors w/turn signal, color keyed, retractable
 - Power windows, Power door lock, Keyless entry
 - Rear seat belts 3PELRx4+2PNRXx1, Rear seat centre arm rest
 - Rear spoiler, Rear parking sensors (2), coloured
 - Rear window defogger, Roof Rails, Side impact beam front and rear
 - Side steps, Spare wheel, floor mounted
 - Split rear seat 2nd row full flat/tumble up, split/space up 3rd row
 - Sun visors driver/passenger, vanity mirror passenger side
 - Urethane steering wheel with audio controls, Tachometer
 - Wiper front, intermittent with timer, Wiper rear
- **Dimension & Weight**
 - LWH : 4705 x 1840 x 1795 mm
 - Wheelbase : 2750 mm
 - Curb weight : 1825 kgs
 - Gross vehicle weight: 2450 kgs
 - Ground clearance: 220 mm
 - Min. turning radius: 5.9 m