

## **Toyota Fortuner 2.7 SR5 Premium**

**Technical details:** 

Model Code TGN51L-EKMSKV

Origin: Indonesia

Engine Petrol, 2694 cc, 4 cyl. In-line DOHC 16V, VVTi, EFi,

Catalyst converter for unleaded fuel

Max output/Torque 158 HP/5200 rpm, 24.6/3800 rpm

Transmission 5-speed manual (floor), Full time 4x4, TORSEN

Limited Slip Differential (Centre)

Tires and disc wheel Tire 265/65R17 on 6.5J 17" alloy wheels

Brakes front/rear Vent. Disc/Drum w/LSPV Suspension front/rear: Double Wishbone / 4-link Coil

Seats 7 seats (2+3+2), fabric

Fuel tank capacity 80L

## **Standard Equipment:**

- ABS brakes
- Air-conditioner, Dual with heater
- Airbag driver/passenger
- AM/FM radio w/single CD, MP3 and 6 speakers + USB and AUX port
- Adjustable seat belt anchors, front
- · Bumper front and rear, color keyed
- Combination meters
- Console box with lid and cup holder
- · Digital clock, Door handles, chromed
- Driver's seat vertical adjustable
- Engine immobilizer, Floor mats new design
- Front seat belts 3PELRx2 + pre-tensioner
- Front fog lamps, Front map lamps, Fuel lid opener
- Green laminated windshield
- Halogen head lamps, Head lamp leveling
- Head rests front 2 and rear 2+2, Heater, front
- High mount stop lamp LED, Inner rear view mirror day/night
- Mud guards front and rear
- Over fenders, color keyed, Power mirrors w/turn signal, color keyed, retractable
- Power windows, Power door lock, Keyless entry
- Rear seat belts 3PELRx4+2PNRXx1, Rear seat centre arm rest
- Rear spoiler, Rear parking sensors (2), coloured
- · Rear window defogger, Roof Rails, Side impact beam front and rear
- Side steps, Spare wheel, floor mounted
- Split rear seat 2<sup>nd</sup> row full flat/tumble up, split/space up 3<sup>rd</sup> row
- Sun visors driver/passenger, vanity mirror passenger side
- Urethane steering wheel with audio controls, Tachometer
- Wiper front, intermittent with timer, Wiper rear

## • Dimension & Weight

• LWH: 4705 x 1840 x 1795 mm

Wheelbase: 2750 mmCurb weight: 1810 kgs

Gross vehicle weight: 2450 kgs

Ground clearance: 220 mm

• Min. turning radius: 5.9 m