## **Toyota Land Cruiser Prado TX 9**



## **Technical details:**

Model Code	LJ150L-GKMEE
Country of origin:	Japan
Engine	Diesel, 2,986 cc, 4-cyl. in-line OHC
Max output/Torque	94 HP/4000 rpm, 20.1 KgM w/2400 rpm
Transmission	5 speed manual transmission
Tires and disc wheel	245/70R17 tires, 17" x 7.5JJ alloy wheel
Brakes front/rear	Ventilated Disc/Ventilated Disc
Suspension:	Front: double wishbone, coil springs, stabiliser bar
	Rear: 4-link Coil springs
Seats	9 seats (3+3+2x2 parallel bench), Upholstery: Fabric
Fuel tank capacity	150 L

## **Standard Equipment:**

- Full time 4WD (3-mode), Limited Slip Differential (Centre Diff.)
- Power steering w/tilt function
- ABS+EBD+BA, Mud guards front and rear
- Airbag, driver/passenger, Color keyed bumpers
- Rear spoiler, High mounted rear stop lamps
- Front wipers, adjustable intermittent
- High mount stop lamp, Rear intermittent wiper
- Rear window defogger w/timer
- Headlamp leveling, manual, Door handles, black
- Head rests driver + co-driver +  $2^{nd}$  row
- Door mounted spare wheel with cover & sticker
- Windshield glass, green acoustic with top shade
- Front grill and outside door handles, black
- Outer mirrors, black, power adjustable w/turn signal
- Console box, Remote fuel lid opener
- Meter illumination control, Power windows, Power mirrors, Keyless entry
- Air-conditioner, manual, Driver's lumbar support, power adjustable
- Driver's seat vertical adjustable
- AM/FM/Cassette/CD/MP3 + 6 speakers and glass integrated antenna
- 2<sup>nd</sup> row seats 40/20/40 split foldable
- Front seat belts 3 PELR x 2 + PT + FL
- 2<sup>nd</sup> row rear seat belts 3 PELR/ALRx3, 3<sup>rd</sup> row parallel seat without seat belts
- Adjustable seat belt anchors, Tachometer, Digital clock
- Inner rear view mirror day/night, sun visors 2, vanity mirror 2
- Air-conditioning w/heater, Engine immobilizer
- Combination meter, Spare wheel carrier hard type & sticker
- Dimension & Weight
- LWH : 4930 x 1885 x 1845 mm (17.15 M3)
- Wheelbase : 2790 mm
- Curb Weight : 2300 kg
- Ground clearance: 220 mm